

The Monimax 5600 is an outstanding choice for both on-site and off-site locations. Featuring UL 291 Level 1 security and an easy-to-use interface, it is a superior option when you need a high-capacity, secure, reliable ATM.

Features

Innovative Design

This elegant ATM grabs customers' attention with its sleek exterior and easy-to-use ergonomic interface. A 15" TFT LCD provides unsurpassed convenience; the Vacuum Fluorescent Display (VFD) maximizes your attention-getting advertising messages.

Reliability

The Monimax 5600 guarantees enhanced security with UL291 Level 1 compliance (and optional security up to EMV Level 1, 2). A built-in surveillance camera is optional.

Non-stop Operation

With high-capacity receipt, journal and cassettes, Monimax 5600 can be deployed both on- and off-premise. It's worry-free 24/7.



Monimax 5600 features reliable performance with functions that include cash withdrawal, card retraction, receipt printing, and electronic or dot-matrix journal printing.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 5600

System Control

- Intel® Pentium® IV processor
- Microsoft® Windows® XP platform
- NDC+, User Application

Communication

- TCP/IP

Customer Display

- 15" color TFT LCD

Optional

- Privacy filter
- Sunlight readable

Input Type

- 4x2 function keys
- PCI EPP (Encrypting PIN Pad)
- ADA compliant

Card Handling

- Dip-type card reader

Optional

- IC card reader
EMV Level 1, 2 compliant
- Anti-skimming
- Motor-driven card reader

Cash Dispensing

- 3,000 notes cassette
(Up to 4 cassettes)
- Bundle retraction
- Automatic shutter

Printers

- 3.1" graphical thermal receipt printer
- Electronic journal
- 5,000 transactions

Optional

- Journal printer

Security

- UL291 Level 1 safe
- Electronic safe lock

Optional

- KABA Mas Cenccon safe lock
- Security camera

Miscellaneous

- Lead-through indicator

Optional

- VFD (Vacuum Fluorescent Display) (standard)
- Heater (optional)

Power Supply

- AC 110 – 240V, 50–60Hz
- Backup battery

Operating Environment

- Temperature: 31°F – 104°F (0°C – 40°C)

Optional

- Humidity: 25%–85%

Dimension and Weight

- Height : 59.3" (1,505 mm)
- Width : 18.5" (470 mm)
- Depth : 29.9" (760 mm)
- Weight : 978 lbs (444 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.