

High-end, advanced, full-function lobby ATM with deposit automation capability.

The 7600FFL offers the newest technology that accepts bundle-note or bundle-check deposits. These optional features save you money and increase customer convenience and service.

Features

Multi-function ATM

Monimax 7600FFL offers envelope-free deposits with the latest check-scanning and bundle note deposit technology.

Reliability

Monimax 7600FFL guarantees high reliability and safety by meeting demanding standards such as PCI Compliant Encrypting PIN pad (Triple DES), EMV and a UL291 Level 1 safe.

User Friendly Design, Earth Friendly Features

Compliant with ADA requirements, Monimax 7600FFL is ergonomically designed to enable convenient transactions for its users. It also offers easy operation with a 15" TFT LCD display. Plus, the 7600FFL saves tons of paper over time, giving you the power to build your image as an earth friendly company.

The 7600FFL is the ideal lobby solution for high-volume transactions, enabling your customers to access their cash 24/7.



The Monimax 7600FFL is a customer-centric earth friendly ATM with the power to grow with your business.



Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

System Control

- Intel® Pentium® IV processor
- Microsoft® Windows® XP platform
- NDC+, User Application

Communication

- TCP/IP

Customer Display

- 15" color TFT LCD

Optional

- Privacy filter
- Sunlight readable

Input Type

- 4x2 function keys
- PCI complaint EPP
- ADA compliant

Card Handling

- Dip-type card reader

Optional

- IC card reader
EMV Level 1, 2 compliant
- Anti-skimming
- Motor-driven card reader
- Contact-less card reader

Supervisor Operation

- 15" TFT color LCD, touch screen

Cash Dispensing

- 3,000 notes cassette
(Up to 4 cassettes)
- Bundle retraction
- Automatic shutter

Depository

- Bundle check acceptor
 - Bundle note acceptor
- Optional**
- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- 5,000 transactions
- Electronic journal

Optional

- Statement printer

Security

- UL 291 Level 1
- Mechanical combination lock

Optional

- Electronic lock
- KABA Mas Cencon lock

Optional

- Heater
- Barcode reader

Power Supply

- AC 110 – 240V, 50–60Hz
- Back-up battery
(Reserving last transaction & safe shutdown)

Operating Environment

- Temperature: 31°F – 104°F

Optional

- Humidity: 25% – 85%

Dimension and Weight

- Height : 66.1" (1,677.9 mm)
- Width : 30.3" (770 mm)
- Depth : 44.2" (1,121.7 mm)
- Weight : 1,984.1 lbs (900 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

